



All the patents are held accountable counterfeiting.

## Features



## Green Power

- Standard/Din Rail Mounting Dual Purpose
- No-load Consumption is lower than 0.3W
- Comply with High Efficiency Power 80Plus Criterion
- Comply with 2010. Energy Conservation Power Erp Regulation
- Convection cooled high reliability
- 100% burn-in test
- 2 years warranty
- Output modify range: 3V~200VDC

DIMENSIONS: 103(H)\*74(D)\*45(W)mm

WEIGHTS: 181g

## General specifications

## INPUT

Input range	180~264VAC 255~380VDC
Input frequency	47~63Hz
Max. I/P current / Inrush current (25°C)	1.0A/40A@220VAC

## OUTPUT

Hold-up time	13ms
Short protection	Autorecovery
Over load protection	Automatic power limited

## Detail specifications

## 100 Watts

MODEL	O/P Volt Adj. ± %	Load(Current)			Ripple & Noise <sup>4</sup>	Line REG. <sup>2</sup>	Load REG. <sup>3</sup>	Efficiency <sup>5</sup>	O.V.P
		Min.	Rated	Max.					
NL1100D-05	V : +5V ±10%	0A	14A	20A (Peak 30s)	180mV	±1%	±1%	81% Ref.	7.13 ~ 7.88V
NL1100D-06	V : +6V ±10%	0A	11.6A	16.6A (Peak 30s)	180mV	±1%	±1%	81% Ref.	7.13 ~ 7.88V
NL1100D-12	V : +12V ±10%	0A	8.3A	8.3A	180mV	±1%	±1%	83% Ref.	17.1 ~ 18.9V
NL1100D-24	V : +24V ±10%	0A	4.1A	4.1A	240mV	±1%	±1%	88% Ref.	31.4 ~ 34.7V

## CE Standards

EN 55032, EN 55035,  
EN 61000-3-2, EN 61000-3-3,  
(EN 61000-4-2, EN 61000-4-3,  
EN 61000-4-4, EN 61000-4-5,  
EN 61000-4-6, EN 61000-4-8,  
EN 61000-4-11)  
LVD: EN 62368-1

## Safety Standards



UL 508 APPROVAL



CE Marking

## Environments

Operating Temperature -15 ~ 50°C, Ambient  
Operating Humidity 20 ~ 90% RH, No Condensing  
Storage Temperature -20 ~ 85°C, Ambient  
Vibration 2G, 10~500Hz, 3 axes

## NOTE

1. Each output can provide up to maximum load, but total load can not exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. With ● are CE safety approval, but no UL safety approval.
8. Output Voltage Adjustable is measured on 5% of rated load.
9. Reign Power reserve the right to change specifications at any time without notice.

WEB : <http://www.switching-powers.com>  
E-mail : [rp21003f@ms7.hinet.net](mailto:rp21003f@ms7.hinet.net)


Tel : 886-2-22997550  
Fax : 886-2-22997596

**REIGNPOWER**  
S.M.P.S



All the patents are held accountable counterfeiting.

Mechanical Details



Panel Designation

CASE NO. : CS024DR  
 UNIT : mm  
 DIMENSION : 103(H)\*74(D)\*45(W)  
 MATERIAL : PLASTIC  
 COLOR : GRAY

Symbol	Description
N	Neutral Terminal Of AC Input (No Polarity At DC Input)
L	Line Terminal Of AC Input (No Polarity At DC Input)
⊕	Grounding (Earth)
-	DC Negative Output Terminal
+	DC Positive Output Terminal
DC ON	Blue LED Indicator
V adj.	Potentiometer For Output Voltage