



## Features



DIMENSIONS : 151(L) x 99(W) x 35(H)mm  
WEIGHTS: 500g

- Convection cooled
- 100% burn-in test
- MOSFET designed
- 2 years Warranty
- **Output modify range: 3V~200VDC**
- **Split rail & Series connection possible**

## General specifications

INPUT

Input range	90~264VAC 127~380VDC
Input frequency	47~63Hz
Inrush current (25° C)	20A/110VAC 40A/220VAC

OUTPUT

Hold-up time	16mS
Short protection	Autorecovery
Overload protection	Automatic power limited
Over voltage protection	Optional

## Detail specifications

100 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) <sup>1</sup>			Ripple & Noise <sup>4</sup>	Line REG. <sup>2</sup>	Load REG. <sup>3</sup>	Efficiency <sup>5</sup>	O.V.P
		Min.	Rated	Max.					
SLP1100-12F	V : +12V ±10%	0A	8.3A	8.3A	120mV	±1%	±1%	85% Ref.	17.1 ~ 18.9V
SLP1100-24F	V : +24V ±10%	0A	4.2A	4.2A	240mV	±1%	±1%	89% Ref.	31.4 ~ 34.7V
SLP1100-48F	V : +48V ±10%	0A	2.1A	2.1A	480mV	±1%	±1%	91% Ref.	64.6 ~ 71.4V
SLP21001F	V1 : +12V±10% V2 : +5V	0A 0A	7.1A 3A	7.1A 3A	120mV 40mV	±1%	±1%	85% Ref.	17.1 ~ 18.9V 5.8 ~ 7.0V
SLP21002F	V1 : +24V±10% V2 : +5V	0A 0A	3.55A 3A	3.55A 3A	240mV 40mV	±1%	±1%	85% Ref.	31.4 ~ 34.7V 5.8 ~ 7.0V
SLP21003F	V1 : +24V±10% V2 : +12V	0A 0A	3.17A 2A	3.17A 2A	240mV 80mV	±1%	±1%	85% Ref.	31.4 ~ 34.7V 15 ~ 18V

## CE Standards

EN 55032, EN 55035,  
EN 61000-3-2, EN 61000-3-3,  
(EN 61000-4-2, EN 61000-4-3,  
EN 61000-4-4, EN 61000-4-5,  
EN 61000-4-6, EN 61000-4-8,  
EN 61000-4-11)  
LVD: EN 62368-1

## Safety Standards

 UL 60950 Meet

 CE Marking

## Environments

Operating Temperature -15 ~ 50°C, Ambient  
Operating Humidity 20 ~ 90% RH, No Condensing  
Storage Temperature -20 ~ 85°C, Ambient  
Vibration 2G, 10~500Hz, 3 axes

NOTE

1. Each output can provide up to maximum load, but total load can not exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. Output Voltage Adjustable is measured on 5% of rated load.
8. Reign Power reserve the right to change specifications at any time without notice.